Pro-Line AllClean

Cleaning Crystals Packaging: Available in 2 lbs. & 8 lbs Containers

- * Use on Grout, Tile, Masonry
- * Use Interior or Exterior
- * V.O.C. 0% by weight before dilution
- * Easy to use/Fast acting
- * Removes efflorescence

 Usage: AllClean is a sulfamic acid crystal that when mixed with water is used for cleaning tile, grout, and masonry surfaces.

Suitable surfaces:

- Acid-Resistant Glazed Tile
- Quarry Tile
- Unglazed Ceramic Tile
- Porcelain Tile
- Cement Grout & Mortar
- Masonry

 Allow newly grouted installation to cure a minimum of 10 days before use.

• TEST A SMALL AREA According to application instructions to determine desired results.

◆ APPLICABLE STANDARDS: The recommended cleaning solution of the American National Standards Institute (ANSI A108), National Tile Contractors Association A-7, and the Materials and Methods Standards Association Bulletin No. 6. Color — White Fine granules.

•Mix: Mix slowly to avoid inhaling fine particulate matter. Mix 2 pounds of AllClean to 5 gallon of water and mix well being sure all the crystals are dissolved. Water should be room temperature.

Application: Pre-wet the surface with clean water. Apply the solution to the surface and let stand for 3-5 minutes, and then agitate the surface with a brush. Do not allow the solution to dry on the surface. Work small areas. Extract all dirty remains with a wet vacuum system. Multiple applications may be necessary. After extracting the AllClean solution, rinse thoroughly with clean water.

Storage: One year if kept dry and sealed. Store in original container only. Store in temperatures between 40 °F and 90 °F (4 °C and 32 °C). ◆Caution: Do not mix with ammoniate cleaners as harmful fumes may result. Not recommended for use on very porous tile, stone or masonry. Acids, no matter how mild, may etch, lighten or alter the color of tile, cementitious products and natural stone surfaces. Repeated acid washing may damage some surfaces. Do not use AllClean on acid sensitive grout colors: #86 Ocean Blue, and #140 Black Jade. Not recommended for highly porous tile such as Saltillo.

◆Safety: May cause eye, skin, or lung injury. CAUTION: Sulfamic acid and its solutions cause eye burns and irritate the nose, throat and skin. Do not get into eyes. Avoid contact with skin and clothing. Minimize exposure by wearing eye goggles and rubber gloves when handling. KEEP OUT OF REACH OF CHILDREN. Before using, users shall determine the suitability of the product for their intended use. Users assume all risks and liability whatsoever in connection therein.

Warranty: Bonded Materials Company ("Bonded Materials") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Bonded Materials sole liability under this warranty shall be limited to the replacement of the product. The statements, recommendations, and technical information provided are furnished without warranty. representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Bonded Materials makes no warranty for a particular purpose with respect to product sold herein, except guality of components shall be in accordance with Bonded Materials standards. It is expressly understood and agreed that the buyer's sole and exclusive remedy shall be replacement of defective products. Handling and actual use of product are beyond the control of Bonded Materials, therefore, no warranty is made. expressed or implied, as to the results obtained from use of the product or against any claims for infringement of patents resulting from the use of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Bonded Materials printed instructions. Bonded Materials makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.



Data Sheets are subject to change without notice. For latest revision, check our website at www.bondedmaterials.com. If an installation or materials should be changed outside the detailed instructions, please contact our technical support dept .for assistance. ♦ Bonded Materials Company ♦ 4330 N. 43rd Ave. Suite B-4 Phoenix, Az.85031 Ph. 623-873-0001 Toll Free 877-726-6333 www.bondedmaterials.com

